



Razer Demolition Tool (GDT)



Features

1. Low-cost, reversible, long-life crushing teeth are quickly and easily replaced, eliminating build-up
2. 4-way indexable cutting blades feature an apex that draws material deeper into the jaw for more efficient cutting
3. Easy-to-change crushing teeth are available in several configurations to maximize performance in any application
4. Lighter weight ensures stable mounting on today's excavators and specialty high-reach machines
5. Short, flat-top head with bolt-on bracket shortens the center of gravity while making it easy to change mounting for different carriers
6. Open lower jaw allows material being processed to easily pass through, preventing jamming
7. Cylinder is reverse-mounted to protect from debris

Applications

- Concrete Recycling
- C & D Processing
- Bridge Demolition
- Wire
- Copper
- Structural Steel
- Demolition
- Rebar
- Aluminum



Model	Weight* kg (lb)	Jaw Opening mm (in)	Jaw Depth mm (in)	Reach** mm (ft. in)	Minimum Excavator Wt. Stick Mount mt (lb)
GDT 190	2,223 (4,900)	787 (31)	838 (33)	2,438 (8' 0")	20 (45,000)
GDT 290	3,175 (7,000)	991 (39)	1,067 (42)	2,794 (9' 2")	30 (66,000)
GDT 390	4,536 (10,000)	1,168 (46)	1,143 (45)	3,200 (10' 6")	41 (90,000)
GDT 590	6,849 (15,100)	1,321 (52)	1,181 (46.5)	3,759 (12' 4")	54 (120,000)

*Weight includes mounting bracket to attach to excavator.

**Distance is measured from the attachment mounting pivot (boom or stick) forward.



1 866 458 0101
smsequipment.com