

**TO PREVENT PREMATURE UNDERCARRIAGE
DAMAGE, LOAD ACCORDINGLY**

| Material | LBS / m³ (yd³) | MAX. / m³ (yd³) |
|---------------------|---|--|
| Asphalt | 2064 (2700) | 3.40 (4.50) |
| Brick, Soft Clay | 2064 (2700) | 3.40 (4.50) |
| Brick, Hard Clay | 2600 (3400) | 2.70 (3.50) |
| Brick, Paving | 2829 (3700) | 2.50 (3.25) |
| Clay, Dry | 1300 (1700) | 5.40 (7.00) |
| Clay, Wet | 2294 (3000) | 3.10 (4.00) |
| Clay & Gravel, Dry | 2064 (2700) | 3.40 (4.50) |
| Coal, Anthracite | 1223 (1600) | 5.70 (7.50) |
| Coal, Bituminous | 994 (1300) | 7.10 (9.25) |
| Concrete, Cinders | 2294 (3000) | 3.10 (4.00) |
| Concrete, Gravel | 3135 (4100) | 2.30 (3.00) |
| Concrete, Limestone | 3135 (4100) | 2.30 (3.00) |
| Concrete, Sandstone | 2982 (3900) | 2.30 (3.00) |
| Concrete, Trap Rock | 3211 (4200) | 2.10 (2.75) |
| Crush Stone | 2064 (2700) | 3.40 (4.50) |
| Earth, Dry Loose | 1453 (1900) | 4.80 (6.25) |
| Earth, Damp Loose | 1605 (2100) | 4.40 (5.75) |
| Earth, Damp Packed | 1988 (2600) | 2.10 (2.75) |
| Earth & Gravel, Dry | 2064 (2700) | 3.40 (4.50) |
| Earth & Gravel, Wet | 2446 (3200) | 2.90 (3.75) |
| Earth & Sand, Dry | 2064 (2700) | 3.40 (4.50) |
| Earth & Sand, Wet | 2446 (3200) | 2.90 (3.75) |
| Granite | 3440 (4500) | 2.10 (2.75) |
| Mud, Dry | 1835 (2400) | 3.80 (5.00) |
| Mud, Packed | 2370 (3100) | 3.10 (4.00) |
| Mud, Wet | 2217 (2900) | 3.10 (4.00) |
| Sand, Dry Loose | 1988 (2600) | 3.40 (4.50) |
| Sand, Wet | 2446 (3200) | 2.90 (3.75) |
| Sandstone | 3058 (4000) | 3.10 (4.00) |
| Shale | 3364 (4400) | 2.10 (2.75) |
| Tile | 2294 (3000) | 3.10 (4.00) |
| Mats, Construction | 2294 (3000) Ea. | 4 PCS. |