

TERRAMAC® RT6 RUBBER TRACK CARRIER

Standard RT6 Specs

The Terramac® RT6 features a 12,000 lb. carrying capacity and is built to be nimble while providing the power needed to accomplish the task at hand. This unit can accommodate a wide variety of support equipment making it ideal for an array of projects including pipeline, environmental, utility, general construction and many more.



DIMENSIONS	
Full Length	16' 2"
Full Width	8' 2"
Wheel Base	6' 2"
Min Ground Clearance	1' 6"
Front Overhang	2' 6"
Track Width	23.6"
Track Length	12' 1"
Full Height	9' 6"
Height of Dump Bed	6' 6"
Height of Dump Bed Side (Vessel)	1' 6"
Length of Dump Bed (Vessel)	9' 2"
Width of Dump Bed (Vessel)	7' 6"
Dumping Angle	60°
Machine Weight (with bed)	17,900 lbs.

ENGINE	
Manufacturer	Cummins
Model	QSB 4.5
Displacement	272 cu. in.
Horsepower	130 HP
Electrical System	12 VDC
Battery	(2) GRP 31, 1125 CCA
Fuel Capacity	40 gallons

HYDRAULICS	
Transmission	HST
Piston Pump Capacity (x2)	32 gpm / side
Relief Valve Piston Pump	5,500 PSI
Tandem Gear Pump Capacity	
Rear Section (HST Drive)	20 gpm @ 500 PSI
Front Section (Aux Output)	25 gpm @ 2500 PSI

PERFORMANCE	
Max. Carrying Capacity	12,000 lbs.
Travel Speed - 1st Gear	3.5 mph
Travel Speed - 2nd Gear	6.5 mph
Gradability (unloaded)	30%
Turning Radius	8' 1"
Ground Pressure (full capacity)	5.2 PSI
Ground Pressure (unloaded)	3.2 PSI

TERRAMAC[®] RT6 RUBBER TRACK CARRIER

Standard RT6 Units & Dimensions

