



Versi Pro 15 (GVP)



Features

1. Patented pivot system provides a power curve to match each jaw set's primary application
2. 360° rotation comes standard with every Versi Pro
3. Proprietary regeneration valve improves cycle time by up to 33% compared to standard hydraulic systems
4. Each jaw's pivot group stays intact, allowing the use of a press-fit pin design for a stronger, more durable product and making jaw change-outs safe, easy and fast
5. Jaw change-outs in 10 minutes with the couplerstyle connection system

Shear Jaw

- Patented bolt-on piercing tip is replaced in minutes without grinding or welding
- Four-way indexable guide blades, razor blade and primary blades provide four useable cutting edges
- Exclusive dual guide blade system accommodates heat expansion at the tip while maintaining tighter tolerances where the primary cutting blades pass



Shear Jaw Applications

- Scrap Processing
- Demolition
- Rebar
- Wire
- Tires
- Many Types of Non-ferrous

Cracker Jaw

- Offset teeth rows maximize the ability to downsize material
- Patented pivot geometry creates peak power when jaws are near wide open, where it's most needed to crush concrete



Cracker Jaw Applications

- Demolition
- Concrete Recycling
- C & D Processing

Model	Weight* kg (lb)	Jaw Opening mm (in)	Jaw Depth mm (in)	Reach** mm (ft. in)	Minimum Excavator Wt.	
					Boom Mount mt (lb)	Stick Mount mt (lb)
Shear	1,451 (3,200)	406 (16)	381 (15)	2,261 (7'5")	8 (18,000)	13 (28,000)
Cracker	1,451 (3,200)	635 (25)	635 (25)	2,515 (8'3")	8 (18,000)	13 (28,000)

*Weight includes mounting bracket to attach to excavator. **Distance is measured from the attachment mounting pivot (boom or stick) forward. The GVP 15 body and jaws are available in black only. The stability of each lift class varies between OEM excavator models. Please consult with your Genesis salesperson for recommended carrier models.



1 866 458 0101
smsequipment.com