

Versi Pro 07 (GVP 07)



Features

1. Each jaw's pivot group stays intact, allowing the use of a pressfit pin design for a stronger, more durable product and making jaw change-outs safe, easy and fast
2. 360° rotation comes standard with every Versi Pro
3. The innovative bracket system accommodates a skid steer quick plate or a mini excavator lug plate change-over in 10 minutes
4. Electric over hydraulic system allows for jaw open or close and rotation with one hydraulic circuit
5. Proprietary regeneration valve improves cycle time by up to 33% compared to standard hydraulic systems
6. Jaw change-outs in 10 minutes with the coupler-style connection system

Applications

- Interior demolition
- Scrap processing
- On-site material processing and handling

SKID STEER BRACKET

Skid steer mounting bracket option features a traction grip to provide operator safe entry and exit



SHEAR JAWS

Patented pivot geometry creates peak power for piercing and cutting

Weld-on wear plate and piercing tip

Four-way indexable guide blades and primary blades provide four useable cutting edges



CRACKER JAWS

Patented pivot geometry creates peak power when jaws are fully open, where it's most needed to crush concrete

Open relief design allows concrete to pass through lower jaw



GRAPPLE JAWS

Recessed welds are protected from wear, increasing grapple life

Boxed-tine construction creates a very high strength and lightweight grapple – each tine will withstand the full breakout force of the carrier

Replaceable tine tips are abrasion-resistant

Inside radius matches that of a 55-gallon barrel



WIRE CUTTER JAWS

Bolt-on interchangeable cutting blades can be sharpened and are easily replaced

Curved jaw design gathers material deeper into the jaw for maximum cutting power

Unique self-tensioning pivot group maintains optimal blade clearance

For non-ferrous wire only



Model	Weight* kg (lb)	Jaw Opening mm (in)	Jaw Depth mm (in)	Reach** mm (ft. in)	Minimum Excavator Weight		Minimum Skid Steer Weight mt (lb)
					Boom Mount mt (lb)	Stick Mount mt (lb)	
Shear Jaws	624 (1,375)	292 (11.5)	292 (11.5)	1,676 (5' 6")	5 (12,000)	7 (16,000)	3 (7,000)
Cracker Jaws	628 (1,385)	368 (14.5)	330 (13)	1,727 (5' 8")	5 (12,000)	7 (16,000)	3 (7,000)
Grapple Jaws	644 (1,420)	813 (32)	394 (15.5)	1,803 (5' 11")	5 (12,000)	7 (16,000)	3 (7,000)
Wire Cutter Jaws	565 (1,245)	267 (10.5)	292 (11.5)	1,753 (5' 9")	5 (12,000)	7 (16,000)	3 (7,000)

*Weight includes mounting bracket to attach to excavator. **Distance is measured from the attachment mounting pivot (boom or stick) forward. The GVP 07 body and jaws are available in black only. The stability of each lift class varies between OEM skid steer and mini excavator models. Please consult with your Genesis salesperson for recommended carrier models. Control packages are available for carriers less equipped. Patents: genesisattachments.com/products/patents